

Full Throttle Trailer Sales

Phone: 4062591347  
2506 Phyllis Ln  
Billings, MT  
Email: scottk@fullthrottleautomt.com; cord@fullthrottleautomt.com;  
dathan@fullthrottleautomt.com



2022 Valor Trailers 16TU Tilt 19K Equipment Trailer

|  |                         |                       |
|--|-------------------------|-----------------------|
| Stock#: T6368  | VIN#: 1V9PT2020N1233915 | Year: 2022            |
| Manufacturer: Valor Trailers   | Width: 83" or 6'11"     | Length: 192" or 16'0" |
| Color: WHITE   | #Axles: 2               | Axle Capacity: 0.00   |
| URL: <a href="https://fullthrottletrailersales.com/2022-valor-trailers-16tu-tilt-19k-equipment-trailer-wgXI.html">https://fullthrottletrailersales.com/2022-valor-trailers-16tu-tilt-19k-equipment-trailer-wgXI.html</a> |                         |                       |

|       |             |
|-------|-------------|
| Price | \$15,900.00 |
|-------|-------------|

Description

- 83X16
- GVWR 19,200 lbs
- Capacity (Distributed) 16,280 lbs
- Base Trailer Weight 2,920 lbs
- Frame Construction 5" x 3" Tubular Subframe with Perimeter Rails
- Crossmembers 3" x 1.5" Tubular Crossmembers on 16" Centers
- Hitch 2.5" ID Lunette Eye, Adjustable Height
- Landing Gear 12,000 lb Capacity with Drop Foot
- Safety Chains Qty 2 - 3/8" x 36" Grade 70 High Tensile Strength with Slip Hooks and Safety Latches
- Deck Latch Over-Center Standard Latch and Safety Pin
- Cushion Cylinder 3" x 8" with Internal Metered Flow to Cushion Loading and Unloading
- Load Securement 8 each (4 per side) 1" Diameter D-rings and Stake Pockets
- Tool Compartment Combination Open Tool Tray and Lockable Lid
- Axles Qty 2 - 8,000 lbs Capacity

Hubs 8 - 6.5" Bolt Circle with 5/8" Lug Nuts

Brakes 12-1/4" x 3-3/8" Electric Brakes both Axles with 12 Volt Sealed Breakaway System

Suspension Rubber Torsion

Wheels 17.5" x 6.75" 8 on 6.5" Bolt Pattern

Tires ST215/75R17.5 Radial Load Range H

Finished Preparation Sandblast

Finish Coating 1 Stage Zink Based Paint

Electrical Phillips Sealed Harness System with Rubber Isolated LED Lighting

Decking 2" Rough Surface No.1 Grade Fir with Fasteners at every other Crossmember

Decking Width 82.5" Between Fenders